


# PMMA INTRAOCULAR LENSES

ONE PIECE POSTERIOR / ANTERIOR CHAMBER LENSES.




CE 2460




### ES - 100

Optic Diameter : 5.00 mm  
Overall Length : 12.00 mm  
Position Holes : NIL  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*




### ES - 117

Optic Diameter : 6.50 mm  
Overall Length : 12.50 mm  
Position Holes : 2  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*




### ES - 101

Optic Diameter : 5.25 mm  
Overall Length : 12.00 mm  
Position Holes : NIL  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*




### ES - 109

Optic Diameter : 6.50 mm  
Overall Length : 13.00 mm  
Position Holes : 2  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*  
**(ES - 108 : NO HOLE)**




### ES - 107

Optic Diameter : 5.50 mm  
Overall Length : 12.50 mm  
Position Holes : NIL  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*




### ES - 112

Optic Diameter : 6.50 mm  
Overall Length : 13.50 mm  
Position Holes : 2  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*  
**(ES - 111 : NO HOLE)**




### ES - 204

Optic Diameter : 6.00 mm  
Overall Length : 12.50 mm  
Position Holes : 2  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*  
**(ES - 203 : NO HOLE)**



### EA - 501

Optic Diameter : 6.00 mm  
Overall Length : 12.50 mm  
Position Holes : NIL  
Haptic Shape : MOD - S  
A Constant : 115.1\*  
A/C Depth : 2.9 mm\*



### ES - 105

Optic Diameter : 6.00 mm  
Overall Length : 13.00 mm  
Position Holes : 2  
Haptic Shape : MOD - C  
A Constant : 118.0\*  
A/C Depth : 4.9 mm\*  
**(ES - 106 : NO HOLE)**

### CUSTOM DESIGN :

**Versatility of our precise advanced technology allows us to produce your own design with utmost accuracy. Our engineering department would be glad to work with you to design the IOL & CTR that best fits your customers' needs.**

Sterilization : Ethylene Oxide Gas (Dry).  
"A" Constant & A/C Depth \* : Estimated Values.  
Haptic Design : Step Vault.

- Diopters Range**
- (a) Regular range : (1) +7 to +35D in 0.5D increments in equiconvex optic
  - (b) Extreme range : (1) +1 to +6D & -1 to -10D in 1.0D increment in concave-convex optic
  - (2) 0 D in plano optic
  - (3) For model availability contact area distributor

**EAGLE OPTICS PVT. LTD.**

EL 140/141, MIDC MAHAPE, NAVI MUMBAI - 400710, INDIA. TEL: 91-22-27619231, 27619218, FAX: 27687437  
e-mail: eagle@eagleopticsltd.com, Website: www.eagleopticsindia.com

**EAGLE**  
LIGHT TOWARDS SIGHT